

Q2 CUSTOMIZABLE KEYBOARD USER MANUAL

Knob Version

Fully Assembled Version

Keyboard

1x Fully Assembled Keyboard

Including

1x Aluminum Case

1x PCB

1x Steel Plate

1x Sound Absorbing Foam

1x Case Foam

12x Gaskets (8 Installed and 4 in the Box)

4 Sets x Stabilizers

1 Set x Keycaps (PBT Double-shot)

1 Set x Switches (Gateron G Pro)

Cable

1x Type-C to Type-C Cable

1x Type-A to Type-C Adapter

Tools

1x Switch Puller

1x Keycap Puller

1x Screwdriver

1x Hex Key



Barebone Version

Keyboard Kit

1x Keyboard Kit (Without Keycaps & Switches)

Including

1x Aluminum Case

1x PCB

1x Steel Plate

1x Sound Absorbing Foam

1x Case Foam

12x Gaskets (8 Installed and 4 in the Box)

4 Sets x Stabilizers

Cable

1x Type-C to Type-C Cable 1x Type-A to Type-C Adapter


Tools


1x Switch Puller

1x Keycap Puller

1x Screwdriver

1x Hex Key






QUICK START GUIDE

If you are a Windows user, please find the appropriate keycaps in the box, then follow the instructions below to find and replace the following keycaps.

Mac / Windows



1 Switch To The Right System

Please make sure the system toggle on the top left corner has been switched to the same system as your computer's operating system.



2 The VIA Key Remapping Software

Please visit <u>caniusevia.com</u> to download the latest VIA software to remap the keys. If the VIA software cannot recognize your keyboard, please reach out to our support to get the instruction.



3 The Layers

There are five layers of key settings on the keyboard.


The layer 0 is for the Mac system.

The layer 1 is for the Windows system.

The layer 2 is for the Mac Multimedia keys.

The layer 3 is for the Windows Multimedia keys.

The layer 4 is for the Function keys.



If your system toggle is switched to Mac, then the layer 0 will be activated.



If your system toggle is switched to Windows, then the layer 1 will be activated.



Kev.

4 Multimedia Key and Function Key



Function keys

F1 / F2 / F3 / F4 / F5 / F6 / F7 / F8 / F9 / F10 / F11 / F12


In order to get Multimedia Key, you need to press fn1 and

In order to get Function Key, you need to press fn2 and




5 The Backlight

Press fn1 + Q to change the lighting effect




Press fn1 + tab to turn the backlight on/off.




6 Adjust The Backlight Brightness

fn1 + W to increase the backlight brightness



fn1 + S to decrease the backlight brightness




7 Adjust The Backlight Speed

Press fn1 + T to increase the light effect speed



Press fn1 + G to decrease the light effect speed



8 Warranty

The keyboard is highly customizable and easy to be rebuilt. If anything goes wrong with any of the keyboard components of keyboard during the warranty period, we will only replace the defective parts of the keyboard, not the whole keyboard.




9 Watch The Building Tutorial On Our Website

If you are building the keyboard for the first time, we highly recommend you watch the building tutorial video on our website first, then start building the keyboard yourself.



10 Factory Reset



Troubleshooting? Don't know what's going on with the keyboard?


- 1) Try factory reset by pressing fn1 +J +Z (for 4 seconds)
- ② Download the right firmware for your keyboard from our website. Remove the power cable from the keyboard.
- (3) Remove the space bar keycap to find the rest button on the PCB.
- 4 Hold the reset key while plugging in the power cable and then release the reset key. The keyboard now will enter DFU mode.
- (5) Flash the firmware with the QMK Toolbox.
- 6 Factory reset the keyboard again by pressing fn1 + J + Z (for 4 seconds)
- * Step by step guide can be found on our website

Q2 CUSTOMIZABLE KEYBOARD SPECIFICATIONS


Specifications				
Layout	65%			
Switch type	Mechanical			
Width	121 mm			
Length	327.5 mm			
Front height	20 mm (without keycaps)			
Back height	33.8 mm (without keycaps)			
Front height	33.6 mm (with OEM keycaps installed)			
Back height	45.6 mm (with OEM keycaps installed)			
Keyboard feet height	2.4 mm			
Angle	6.5 degree			


Q2 MECHANICAL KEYBOARD OVERVIEW

Mac



Windows







- 1 Type-C Port
- 2 Mac Layout
- ③ Windows Layout

DEFAULT KEY LAYOUT:

LAYER 0: This layer will be activated when your keyboard's system toggle is switched to Mac.




LAYER 1: This layer will be activated when your keyboard's system toggle is switched to Windows.




LAIt = Left Alt LWin = Left Windows RAIt = Right Alt


LAYER 2: This layer will be activated when your keyboard's system toggle is switched to Mac and press the fn1/MO(2) key.



LAYER 3: This layer will be activated when your keyboard's system toggle is switched to Windows and press the fn1/MO(3) key.



LAYER 4: This layer will be activated when you press the fn2/MO(4) key.



KEY DESCRIPTION

Key Description		Key Description	
Scr-	Screen Brightness Decrease	RGBMd+	RGB Mode Next
Scr+	Screen Brightness Increase	RGBMd-	RGB Mode Previous
Bright-	Backlight Decrease	Hue+	Hue Increase
Bright+	Backlight Increase	Hue-	Hue Decrease
Prvs	Previous	RGB SPI	RGB Speed Increase
Play	Play/Pause	RGB SPD	RGB Speed Decrease
Next	Next	MO(1)	Layer 1 will be activated when holding this key
Mute	Mute	MO(2)	Layer 2 will be activated when holding this key
Vol-	Volume Decrease	MO(3)	Layer 3 will be activated when holding this key
Vol+	Volume Increase	MO(4)	Layer 4 will be activated when holding this key
RGB Toggle	Turn Backlight on/off		

Third party input tools are not compatible with the keyboard.

Due to compatibility, versions, brands and drivers of Windows/macOS, functionalities of third Party input tools may be affected while using the keyboard. Please make sure your operating system and drivers are up to date.

Certain fn keys or multimedia keys does not work under Windows/Android mode.

Functionalities of certain multimedia keys may be disabled due to compatibility, versions, brands and drivers of Windows/Android OS.

Safety Precaution:

Keep the product, accessories and packaging parts out of reach of children to prevent any accidents and choking hazards.

Always keep the product dry to avoid corrosion.

Do not expose the product to extreme temperatures below -10°C (5°F) or above 50°C (131°F) to preserve the lifespan of the keyboard.

Keychron, Inc. Dover, DE 19901, United States

Find us at: https://www.keychron.com Support@keychron.com

@keychron

@keychron

y @keychronMK

Designed by Keychron

Made in China